

Universal 4G+

All purpose, best-selling tracker



Unique Features

- **On-Board Connectivity:** All-round 12v/24v compatibility for your vehicle or boat.
- **Worldwide Roaming:** Supports worldwide 4G Cat 1 networks.

- **Wide Range of Accessories:** For body wear, attachments, increased battery life and more.

Two Programmable Buttons

SOS Button

Speed Monitoring

Geofencing

One Account for Managing All of Your Devices

Water resistant

Indoor and Outdoor Tracking

Usage Examples

Vehicles

Loved ones

Outdoor

Boats

Staff

Heavy-Duty Machinery

Specifications

Universal 4G+

Stock Code	TRKM010-C
GSM Platform	UWS6121
GNSS	GPS, Galileo, Beidou, GLONASS, QZSS and SBAS
Bands	TDD LTE: B40, B41(B38) FDD LTE: B1,B2,B3,B4,B7,B8, B26(B18/19/5), B20, B12(B17), B28
Sim Card	Embedded SIM or nano-SIM
Application	iOS / Android / Windows / Mac
Colors	Black
Dimensions	47 mm x 40 mm x 17 mm
Weight	42 gr
Active Battery Life	Up to 12 days, depends on mode of operation and cellular network conditions
Battery Type	Rechargeable Li-ion 600mAh
Operational Temperatures	-20 + 60 °C
Included Attachments	Strap, Clip, Velcro, Magnet, Lanyard
Vehicle Attachment Option	Not included. Installation Kit available.
Wi-Fi	802.11b/g/n
Bluetooth	BLE 5.2
Additional Sensors	Accelerometer
USB Charger	Micro USB 5 Volts 500 mA

Application features

Universal 4G+

Full Data or Alert Only	Full Data
Maps	✓
Real Time Updates	✓
Geo Speed Alerts	✓
Geo Fence Alerts	✓
Travel History Available	Up to 365 days
Alerts	Email, SMS, Push
Nº of Location Samples	Unlimited

Customizable Tracking	✓
Global Tracking	✓
SOS Alarm	✓
Minimal Update Interval	5 Sec
Configurable Alert Button	✓
Play Sound	✓

Network & Data Transfer

Universal 4G+

Network Technology	LTE(4G) CAT1
SIM	Embedded or nano-SIM
Roaming Data	Yes

GNSS Specifications

Universal 4G+

Standards	GPS, Galileo, Beidou, GLONASS, QZSS and SBAS
Receiver Frequency	L1, G1, L1C, B1C
Channels	22 tracking / 66 acquisition channels
Accuracy	< 5 meters (open sky)
Sensitivity	-160dBm tracking sensitivity -147dBm Acquisition sensitivity with cold start
Acquisition Time	Hot Start < 2 seconds (open sky) Cold Start < 24 seconds (open sky)
A-GPS	Supported