

TrackiSlim

Our ultra-slim tracker with enhanced features

Unique Features

- **Light Sensor:** Receive an alert when activated in case luggage or shipment is opened.
- **Real-Time Alerts:** Immediate location change alerts and multiple geofence setups.

Worldwide Coverage

SOS Button

Personal Identity Tag

Geofencing

One Account for Managing All of Your Devices

Durable & Waterproof

Indoor and Outdoor Tracking

Smooth, Slim, Fits into Valuables

Usage Examples

Parcels

Bags

Staff

Luggage

DATASHEET - TrackiSlim Cat1

Specifications	TrackiSlim
Stock Code	TRKM035-C
GSM Platform	UWS6121
GNSS	GPS, Galileo, Beidou, GLONASS, QZSS and SBAS
Bands	TDD LTE: B40, B41(B38) FDD LTE: B1,B2,B3,B4,B7,B8, B26(B18/19/5), B20, B12(B17), B28
Sim Card	Embedded SIM
Application	iOS / Android / Windows / Mac
Colors	Black
Dimensions	86 mm x 54 mm x 6.5 mm
Weight	44 gr
Active Battery Life	Up to 16 days, depends on mode of operation and cellular network conditions
Battery Type	Rechargeable Li-ion 800mAh
Operational Temperatures	-20 to + 60 °C
Included Attachments	Device Lanyard
Vehicle Attachment Option	Not included. Installation Kit available.
Wi-Fi	802.11b/g/n
Bluetooth	BLE 5.0
Additional Sensors	Accelerometer, Light Sensor x2
USB Charger	4-points magnetic charger with USB Interface
Waterproof	IP67

Application features	TRACKISLIM
Full Data or Alert Only	Full Data
Maps	✓
Real Time Updates	✓
Speed Alerts	✓
Geo Fence Alerts	✓
Travel History Available	Up to 365 days
Alerts	Email, SMS, Push
№ of Location Samples	Unlimited

DATASHEET - TrackiSlim Cat1

Customizable Tracking	✓
Global Tracking	✓
SOS Alarm	✓
Minimal Update Interval	5-seconds (in Live Tracking mode)
Configurable Alert Button	✓
Play Sound	✓

Network & Data Transfer	TrackiSlim
Network Technology	LTE(4G) CAT1
SIM	Embedded
Roaming Data	Yes

GNSS Specifications	TrackiSlim
Standards	GPS, Galileo, Beidou, GLONASS, QZSS and SBAS
Receiver Frequency	L1, G1, L1C, B1C
Channels	22 tracking / 66 acquisition channels
Accuracy	< 5 meters (open sky)
Sensitivity	-160dBm tracking sensitivity -147dBm Acquisition sensitivity with cold start
Acquisition Time	Hot Start < 2 seconds (open sky) Cold Start < 24 seconds (open sky)
A-GPS	Supported